

DC Range Overview



DC Range			
MCCB	Voltages	Current	Fault Level
B-Frame	24, 48, 65, 80 Vdc (300 Vdc - switch only, 10 A)	up to 30 A	0.6 kA
C-Frame MKIV	65, 80 Vdc	up to 50 A	4 kA
DD-Frame * (RAU option available)	80 Vdc	up to 400 A	10 kA
QDC / QY (13) *	80, 125 Vdc (250 Vdc up to 50 A)	up to 200 A	10 kA
JS25	80 Vdc	80 to 250 A	25 kA
JS25S	80 Vdc	300 to 750 A	20 kA
L20B	125 Vdc	800 to 1500 A	20 kA
G37D	250, 500 Vdc	15 to 125 A	20 kA (at 500 Vdc)
F37D	250, 500 Vdc	150 to 250 A	20 kA (at 500 Vdc)
K50D	250, 500 Vdc	250 to 400 A	20 kA (at 500 Vdc)
L65D	250, 500 Vdc	500 to 800 A	20 kA (at 500 Vdc)
G150D	250, 500, 750, 1000 Vdc	16 to 160 A	100 kA (at 1000 Vdc)
F150D	250, 500, 750, 1000 Vdc	40 to 250 A	100 kA (at 1000 Vdc)
K150D	250, 500, 750, 1000 Vdc	300 to 630 A	100 kA (at 1000 Vdc)
L150D	250, 500, 750, 1000 Vdc	800 A	100 kA (at 1000 Vdc)

QDC Range (80 Vdc, 125 Vdc) 80 Vdc Circuit Breakers 10 kA Curve U2 Mini Rail Mounting, 57 mm Escutcheon and DIN Rail Mounting, 45 mm Escutcheon

Type	Poles	Voltage	kA	MCB Width (mm)	Std. Pack	Ratings (A)	Price Ea.
QDC -1 (13) (Grey Handle)	1	80 Vdc	10	13 (1 Module)	12	5, 10, 15, 20, 25, 30, 40	TBA
						45, 50, 60	TBA
QDC-2(13) (Grey Handle)	2	80 Vdc	10	26 (2 Modules)	6	5, 10, 15, 20, 25	TBA
						30, 35, 40, 45, 50	TBA
QDC-2(13) (Grey Handle)	2 (Parallel)	80 Vdc	10	26 (2 Modules)	6	80	TBA
						100	TBA
QDC-3(13) (Grey Handle)	3 (Parallel)	80 Vdc	10	39 (3 Modules)	4	125,150	TBA

125 Vdc Circuit Breakers 10 kA Curve U2 Mini Rail Mounting, 57 mm Escutcheon and DIN Rail Mounting, 45 mm Escutcheon

Type	Poles	Voltage	kA	MCB Width (mm)	Std. Pack	Ratings (A)	Price Ea.
QDC -1 (13) (Grey Handle)	1	125 Vdc	10	13 (1 Module)	12	5, 10, 15, 20, 25, 30	TBA
						40, 45, 50, 60	TBA
QDC-2(13) (Grey Handle)	2	125 Vdc	10	26 (2 Modules)	6	5, 10, 15, 20, 25	TBA
						30, 40, 45, 50, 60	TBA
QDC-2(13) (Grey Handle)	2 (Parallel)	125 Vdc	10	26 (2 Modules)	6	80	TBA
						100	TBA

Notes: Contact CBI for details. Full range's data sheets available on www.cbi-lowvoltage.com. Standard discounts are not applicable.
* DIN rail option available.